



TYPE APPROVAL BY :



UK LIFTING POINT-WARNINGS AND ORIGINAL INSTRUCTIONS

DE ANSCHLAGPUNKT-WARNUNG UND ORIGINALBETRIEBSANLEITUNG

FR POINT DE LEVAGE - AVERTISSEMENTS ET INSTRUCTIONS D'APPLICATION

ES CÁNCAMOS GIRATORIOS - ADVERTENCIAS E INSTRUCCIONES ORIGINALES

RU ТАКЕЛЖНЫЙ БЛОК - ПРЕДУПРЕЖДЕНИЯ И ИНСТРУКЦИИ ПО ПРИМЕНЕНИЮ

JP リフティングポイント - 警告および使用説明

KR 리프팅포인트 - 경고및사용지침

中文 側向旋轉吊点使用说明

SE Förankringspunkt VARNINGAR OCH ORIGINALINSTRUKTIONER

YOKE INDUSTRIAL CORP.

An ISO 9001 Registered Company

Kind of attachment	WLL											
	1	2	1	2	1	2	2	2	3-4	3-4	3-4	3-4
Number of legs	1	2	1	2	1	2	1	2	2	2	2	2
Lead direction	0°	0°	30°	30°	50°	50°	0-45°	45°-90°	unlimited	0-45°	45°-90°	unlimited
Item No.	Thread											
8-211-005	M 8	0.3	0.6	0.3	0.6	0.4	0.4	0.2	0.3	0.1	0.05	0.05
8-211-006	M 10	0.5	1.0	0.6	1.2	0.8	0.8	0.6	0.8	0.2	0.05	0.05
8-211-007	M 12	1	2	1	2	1.4	1.4	1	1.4	0.3	0.1	0.1
8-211-012	M 14	1.2	2.4	1.2	2.4	1.7	1.7	1.2	2.0	0.3	0.1	0.1
8-211-015	M 16	1.5	3	1.5	3	2.1	2.1	1.5	2.5	0.3	0.1	0.1
8-211-019	M 18	2	4	2	4	2.8	2.8	2	3.2	0.4	0.2	0.2
8-211-025	M 20	2.5	5	2.5	5	3.5	3.5	2.5	4.0	0.5	0.2	0.2
8-211-040	M 24	4	8	4	8	5.6	5.6	4	6.4	0.8	0.4	0.4
8-211-042	M 27	4	8	4	8	5.6	5.6	4	6.4	0.8	0.4	0.4
8-211-050	M 30	5	10	5	10	7	7	5	8.0	1.0	0.5	0.5
8-211-055	M 36	7	14	7	14	9.8	9.8	7	10.5	1.3	0.7	0.7
8-211-060	M 38	8	16	8	16	11.2	11.2	8	12.0	1.4	0.8	0.8
8-211-100	M 42	10	20	10	20	14	14	10	16	2.0	1.0	1.0
8-211-110	M 42	10	20	10	20	14	14	10	16	2.0	1.0	1.0
8-211-200	M 48	12	24	12	24	16	16	12	18	2.4	1.2	1.2
8-211-220	M 50	12	24	12	24	16	16	12	18	2.4	1.2	1.2
8-211-225	M 54	12.5	25	12.5	25	18.5	18.5	13.5	20.5	2.6	1.3	1.3

Table 1.

Kind of attachment	WLL											
	1	2	1	2	1	2	2	2	3-4	3-4	3-4	3-4
Number of legs	1	2	1	2	1	2	1	2	2	2	2	2
Lead direction	0°	0°	30°	30°	50°	50°	0-45°	45°-90°	unlimited	0-45°	45°-90°	unlimited
Item No.	Thread											
8-212-010	M 8	0.3	0.6	0.3	0.4	0.4	0.3	0.3	0.3	0.05	0.05	0.05
8-212-015	M 10	0.5	1	0.5	1	0.5	0.5	0.5	0.5	0.1	0.1	0.1
8-212-019	M 12	0.6	1.2	0.6	1.2	0.8	0.8	0.6	0.8	0.1	0.1	0.1
8-212-025	M 14	0.8	1.6	0.8	1.6	1.1	1.1	0.8	1.1	0.1	0.1	0.1
8-212-040	M 18	1.2	2.4	1.2	2.4	1.7	1.7	1.2	2.0	0.2	0.1	0.1
8-212-050	M 20	1.5	3	1.5	3	2.1	2.1	1.5	2.5	0.2	0.1	0.1
8-212-055	M 22	1.8	3.6	1.8	3.6	2.5	2.5	1.8	2.8	0.2	0.1	0.1
8-212-110	M 30	2.5	5	2.5	5	3.5	3.5	2.5	4.0	0.3	0.2	0.2
8-212-120	M 36	3	6	3	6	4.5	4.5	3	4.8	0.4	0.2	0.2
8-212-200	M 42	4	8	4	8	6	6	4	8	0.6	0.3	0.3
8-212-220	M 48	5	10	5	10	7	7	5	8.5	0.7	0.4	0.4
8-212-225	M 54	6	12	6	12	8.5	8.5	6	9.5	0.8	0.4	0.4
8-212-250	M 60	7.5	15	7.5	15	11.2	11.2	8	12.5	1.0	0.5	0.5
8-212-270	M 66	8.25	16.5	8.25	16.5	12.5	12.5	9	14	1.1	0.5	0.5
8-212-290	M 72	9	18	9	18	14	14	10	15.5	1.2	0.6	0.6
8-212-300	M 78	10	20	10	20	15.5	15.5	11	16.5	1.3	0.6	0.6
8-212-320	M 84	11	22	11	22	17.5	17.5	12	18.5	1.4	0.6	0.6
8-212-350	M 90	12.5	25	12.5	25	20	20	14	22	1.6	0.7	0.7
8-212-370	M 96	13.5	27	13.5	27	22	22	15	24	1.7	0.7	0.7
8-212-400	M 102	15	30	15	30	24.5	24.5	16	26.5	1.9	0.8	0.8
8-212-420	M 108	16.5	33	16.5	33	27	27	17.5	29.5	2.1	0.8	0.8
8-212-450	M 114	18	36	18	36	30	30	19	32	2.3	0.9	0.9
8-212-480	M 120	20	40	20	40	33	33	21	35	2.5	1.0	1.0
8-212-500	M 126	22.5	45	22.5	45	36	36	23	38	2.8	1.1	1.1
8-212-520	M 132	24	48	24	48	39	39	25	41	3.0	1.2	1.2
8-212-550	M 138	27	54	27	54	42	42	27	44	3.3	1.3	1.3
8-212-570	M 144	30	60	30	60	45	45	29	47	3.6	1.4	1.4
8-212-600	M 150	33	66	33	66	48	48	31	50	3.9	1.5	1.5
8-212-630	M 156	36	72	36	72	51	51	33	53	4.2	1.6	1.6
8-212-660	M 162	39	78	39	78	54	54	35	56	4.5	1.7	1.7
8-212-690	M 168	42	84	42	84	57	57	37	59	4.8	1.8	1.8
8-212-720	M 174	45	90	45	90	60	60	39	62	5.1	1.9	1.9
8-212-750	M 180	48	96	48	96	63	63	41	65	5.4	2.0	2.0
8-212-780	M 186	51	102	51	102	66	66	43	68	5.7	2.1	2.1
8-212-810	M 192	54	108	54	108	69	69	45	71	6.0	2.2	2.2
8-212-840	M 198	57	114	57	114	72	72	47	74	6.3	2.3	2.3
8-212-870	M 204	60	120	60	120	75	75	49	77	6.6	2.4	2.4
8-212-900	M 210	63	126	63	126	78	78	51	80	6.9	2.5	2.5
8-212-930	M 216	66	132	66	132	81	81	53	83	7.2	2.6	2.6
8-212-960	M 222	69	138	69	138	84	84	55	86	7.5	2.7	2.7
8-212-990	M 228	72	144	72	144	87	87	57	89	7.8	2.8	2.8
8-213-000	M 234	75	150	75	150	90	90	59	92	8.1	2.9	2.9
8-213-030	M 240	78	156	78	156	93	93	61	95	8.4	3.0	3.0
8-213-060	M 246	81	162	81	162	96	96	63	98	8.7	3.1	3.1
8-213-090	M 252	84	168	84	168	99	99	65	101	9.0	3.2	3.2
8-213-120	M 258	87	174	87	174	102	102	67	104	9.3	3.3	3.3
8-213-150	M 264	90	180	90	180	105	105	69	107	9.6	3.4	3.4
8-213-180	M 270	93	186	93	186	108	108	71	110	9.9	3.5	3.5
8-213-210	M 276	96	192	96	192	111	111	73	113	10.2	3.6	3.6
8-213-240	M 282	99	198	99	198	114	114	75	116	10.5	3.7	3.7
8-213-270	M 288	102	204	102	204	117	117	77	119	10.8	3.8	3.8
8-213-300	M 294	105	210	105	210	120	120	79	122	11.1	3.9	3.9
8-213-330	M 300	108	216	108	216	123	123	81	125	11.4	4.0	4.0
8-213-360	M 306	111	222	111	222	126	126	83	128	11.7	4.1	4.1
8-213-390	M 312	114	228	114	228	129	129	85	131	12.0	4.2	4.2
8-213-420	M 318	117	234	117	234	132	132	87	134	12.3	4.3	4.3
8-213-450	M 324	120	240	120	240	135	135	89	137	12.6	4.4	4.4
8-213-480	M 330	123	246	123	246	138	138	91	140	12.9	4.5	4.5
8-213-510	M 336	126	252	126	252	141	141	93	143	13.2	4.6	4.6
8-213-540	M 342	129	258	129	258	144	144	95	146	13.5	4.7	4.7
8-213-570	M 348	132	264	132	264	147	147	97	149	13.8	4.8	4.8
8-213-600	M 354	135	270	135	270	150	150	99	152	14.1	4.9	4.9
8-213-630	M 360	138	276	138	276	153	153	101	155	14.4	5.0	5.0
8-213-660	M 366	141	282	141	282	156	156	103	158	14.7	5.1	5.1
8-213-690	M 372	144	288	144	288	159	159	105	161	15.0	5.2	5.2
8-213-720	M 378	147	294	147	294	162	162	107	164	15.3	5.3	5.3
8-213-750	M 384	150	300	150	300	165	165	109	167	15.6	5.4	5.4
8-213-780	M 390	153	306	153	306	168	168	111	170	15.9	5.5	5.5
8-213-810												